

RECTANGULAR HOUR COUNTERS



TYPES: 250.2/AC VOLTS & 260.2/DC VOLTS (36x24mm)
252.2/AC VOLTS & 262.2/DC VOLTS (48x24mm)
604.2/AC VOLTS & 609.2/DC VOLTS (54x29mm)



FEATURES

- Standard IP65 front
- Optional IP65 gasket
- Ratchet fixing clamp
- Screw terminals
- Black front
- Seven digits

DESCRIPTION

Rectangular seven digit hour counters either in front bezel sizes of 36x24mm, 48x24mm or 54x29mm. Front sealed as standard to IP65 with additional optional IP65 panel sealing gasket. Supplied as standard with screw terminals but with the option of 6.3x0.8mm push on terminals.



STANDARD SPECIFICATIONS

Counting range:	99999.99h
AC Voltages:	12, 24, 110, 230, 400V (±10%)
Frequency:	50Hz or 60Hz (specify)
DC Voltages:	12-24VDC, 10-50VDC, 50-120VDC
Current:	AC 8mA, DC 5-15mA
Protection Class:	IP65 front, IP00 terminals
Temp range:	-30°C to +70°C,
CE marked:	Yes
Terminations:	Screw

OPTIONS ON REQUEST

(special P/No's & prices may apply)

- Grey faced
- 6.3x0.8mm push on terminations
- Dual 50/60Hz AC versions
- 100Hz versions
- Customer logos
- Type 604 & 609 flying lead cable termination
- UL, CSA, VDE marked

ORDERING INFORMATION

- 250.2 / AC Volts 12, 24, 110, 230VAC (Specify 50Hz or 60Hz)
- 252.2 / AC Volts 12, 24, 110, 230VAC (Specify 50Hz or 60Hz)
- 604.2 / AC Volts 12, 24, 110, 230, 400VAC (Specify 50Hz or 60Hz)
- 260.2 / DC Volts 12-24VDC
- 262.2 / DC Volts 12-24VDC
- 609.2 / DC Volts 10-50VDC, 50-120VDC
- IP65 36x24mm gasket
- IP65 48x24mm gasket
- IP65 54x29mm gasket

