

DC QUARTZ 56mm DIA. FRONT BEZEL HOUR COUNTERS



TYPES: 587.10.2/DC VOLTS (Black plastic front bezel ring)
587.2/DC VOLTS (Black metal front bezel ring)



FEATURES

- IP65 front
- 56mm DIA. bezel size
- Mounting hole DIA. 52mm
- Seven digits
- Push on terminations
- 10-80VDC standard one unit
- Operation indication
- Damping rings available

DESCRIPTION

DC quartz operated hour run counters, 56mm diameter front bezel size. These hour counters are particularly suited to "automotive" applications, the front bezel and mounting dimensions complimenting other automotive style instrumentation such as temperature and oil pressure gauges. Versions suitable for 60mm diameter hole mounting are available on request along with optional 72mm diameter hole mounting versions complete with rubber damping rings for high vibration and impact applications such as heavy plant machinery and railway locomotives.

STANDARD SPECIFICATIONS

Counting range:	99999.99h
DC Voltages:	2-20V, 10-80V, 80-220V
Current:	0.5-27mA
Protection class:	IP65 front, IP00 terminals
Temp range:	-40°C to +80°C
CE marked:	Yes
Terminations:	Push on 6.3x0.8mm

OPTIONS ON REQUEST

(special P/N0's & prices may apply)

- Sweep hand min. indication
- 60mm diameter hole mounting (64mm front bezel size)
- Rubber damping rings (72mm diameter hole mounting)
- Chromed metal front bezel rings
- Screw terminal connection
- Customer logos

ORDERING INFORMATION

587.10.2 / DC Volts	2-20V, 10-80V*, 80-220VDC
587.2 / DC Volts	2-20V, 10-80V*, 80-220VDC

* Standard unit

