FOX60.15

Moulded case current transformers, for primary currents from 400 Amps to 1600 Amps. With built in sliding sealable terminal covers.

FEATURES


- Bus-bar or foot mounted
- Built in sliding sealable terminal covers
- Transformer width 85mm
- Max conductor size 46mm dia.
- Max bus-bar size 60x15mm or 50x30mm
- 1 Amp or 5 Amp secondaries

| P/No. | CLASS | VA |
|-----------------|-------|----|
| F0X60.15 400/5 | 1 | 5 |
| F0X60.15 500/5 | 1 | 5 |
| FOX60.15 600/5 | 1 | 5 |
| F0X60.15 800/5 | 1 | 10 |
| F0X60.15 1000/5 | 1 | 15 |
| F0X60.15 1200/5 | 1 | 15 |
| F0X60.15 1500/5 | 1 | 15 |
| F0X60.15 1600/5 | 1 | 15 |

All of the above ratios are available as Class 0.5 and Class 0.2 to special order, please consult our sales office.







FOX60.3

Moulded case current transformers, for primary currents from 400 Amps to 2000 Amps. With built in sliding sealable terminal covers.


FEATURES

- Bus-bar or foot mounted
- Built in sliding sealable terminal covers
- Transformer width 90mm
- Max bus-bar size 60x30mm
- 1 Amp or 5 Amp secondaries

| P/No. | CLASS | VA |
|----------------|-------|----|
| FOX60.3 400/5 | 1 | 5 |
| F0X60.3 500/5 | 1 | 5 |
| FOX60.3 600/5 | 1 | 5 |
| FOX60.3 800/5 | 1 | 10 |
| F0X60.3 1000/5 | 1 | 10 |
| F0X60.3 1200/5 | 1 | 10 |
| F0X60.3 1500/5 | 1 | 15 |
| F0X60.3 1600/5 | 1 | 15 |
| F0X60.3 2000/5 | 1 | 15 |

All of the above ratios are available as Class 0.5 and Class 0.2 to special order, please consult our sales office.





Tel: 0161 626 5316 / 01276 25858