

Sumo Potato Preparation

RIPPA

Ideally suited to the potato grower the Sumo Rippa is used after ploughing to mix and aerate the soil ahead of bedformers or tillers, also for primary cultivation post-harvest. Designed to work down to 14-16in deep to remove plough pan compaction, the Rippa is available in 3m and 4m rigid, plus 4m, 5m and 6m hydraulic folding versions.



The legs are mounted on a 150mm x 150mm x 10mm hot-formed steel frame, with the front row also incorporating a pair of resin filled depth wheels regulated by a unique pin system.



Reversible points fitted as standard are 80mm units, and are angled at 45° to produce an aggressive upward soil movement.

All models use three rows of 700mm long legs manufactured from 30mm steel. These are shear bolt protected, with a carrier for spare bolts mounted on the implement's headstock.



MODEL	WORKING WIDTH	TRANSPORT WIDTH	LEGS	LEG SPACING	TYPE
Rippa 3	3.0m	3.0m	11	270mm	Rigid
Rippa 4	4.0m	4.0m	15	270mm	Rigid
Rippa 4F	4.0m	3.0m	15	270mm	Hyd Folding
Rippa 5F	5.0m	3.0m	19	270mm	Hyd Folding
Rippa 6F	6.0m	3.0m	23	270mm	Hyd Folding

Sumo Potato Preparation



Reintroduced from Sumo, the 2 and 4 bed Sumoforma's

- The body features the largest mouldboards and the widest share on the market, designed to create steep sides with a wide furrow bottom allowing normal wheel/tyre equipment to be used on subsequent operations.
- All bodies have top forming lids.
- Integral bar point subsoiling enabling soil to be loosened below the furrow bottom and to help keep the machine running in a straight line.
- The bar point is held in place by a hardened pin. Once removed the point can be dropped down to any depth and is especially shaped to allow a replacement to be welded to it enabling all of the material to be worn away.
- The 4 Bed Sumoforma is designed to form four beds in one pass i.e. 3 full and 2 halves.
- Both Sumoformas have telescopic toolbars as an option to run a bed loosening tine through the outer half beds.
- The 4 bed Sumoforma comes complete with dual depth control wheels, meaning on even the roughest ploughing the depth is constant.
- Cat 3 and 4 linkage are standard on the 4 bed Sumoforma enabling the biggest tractors to be used to help in spring cultivations.
- Leg protection is either Auto Rest or Shear Pin.
- Bed widths from 1.7m.

MODEL
2 Bed Sumoforma Auto Reset
2 Bed Sumoforma Shear pin
Markers for the above pair
BLT telescopic – extensions for above pair
Bed loosening tine Trio type – each



MODEL
2 Bed Sumoforma Auto Reset
4 Bed Sumoforma Shear Pin
Markers for above pair
BLT Telescopic – extensions for above pair
Bed loosening tine Trio type – each

