

FXD DYNA[®] SUPER GLIDE[®] MODEL SPECIFICATIONS¹»



DIMENSIONS

Length	92.80 in. (2357.12 mm)
Overall Width	36.70 in. (932.18 mm)
Overall Height	48.50 in. (1231.90 mm)
Seat Height:	
• Laden ²	26.30 in. (668.02 mm)
• Unladen	26.50 in. (673.10 mm)
Ground Clearance	4.60 in. (116.84 mm)
Rake (steering head)	29°
Fork Angle	29°
Trail	4.70 in. (119.38 mm)
Wheelbase	64.20 in. (1630.68 mm)

Tires (Michelin[®] Scorcher™ "31" front and rear):

- Front – Scorcher™ "31" 100/90-19 57H
- Rear – Scorcher™ "31" 160/70-17 73V

Fuel Capacity **4.70 gal.** (17.79 L)
(warning light at approximately 0.9 gal.)

Oil Capacity (w/filter) **3 qts.** (2.84 L)

Transmission Capacity **1 qts.** (0.95 L)

Primary Chain Case Capacity³ **1 qts.** (0.95 L)

Weight:

- As Shipped **632 lbs.** (286.68 kg)
- In Running Order **663 lbs.** (300.74 kg)
- Gross Vehicle Weight Rating **1085 lbs.** (492.16 kg)
- Gross Axle Weight Rating:
- Front **390 lbs.** (176.90 kg)
- Rear **695 lbs.** (315.25 kg)

ENGINE

Engine ⁴	Air-cooled, Twin Cam 96™
Valves	Pushrod-operated, overhead valves with hydraulic, self-adjusting lifters; two valves per cylinder
Bore x Stroke	3.75 in. x 4.38 in. (95.25 mm x 111.25 mm)
Displacement ³	96 cu. in. (1584 cc)
Compression Ratio	9.2:1
Fuel System ⁵	Electronic Sequential Port Fuel Injection (ESPFI)
Air Cleaner	Fiberglass Media, washable
Lubrication System	Pressurized, dry-sump

DRIVETRAIN

Primary Drive	Chain, 34/46 ratio
Final Drive ⁶	Belt, 32/66 ratio
Clutch	Multi-plate, wet
Transmission	6-Speed Cruise Drive [®]
Gear Ratios (overall):	U.S.
• 1st	9.311
• 2nd	6.454
• 3rd	4.793
• 4th	3.882
• 5th	3.307
• 6th	2.790

CHASSIS

Frame	Mild steel, tubular frame; rectangular section backbone; stamped, cast, and forged junctions; forged fender supports; MIG welded
Swingarm	Mild steel, rectangular tube sections, stamped junctions; MIG welded
Front Forks	49 mm with polished aluminum fork triple clamp and dual-rate springs
Rear Shocks	Coil-over shock
Wheels:	Silver, 10-spoke Cast Aluminum
• Front	19 in. x 2.50 in. (482.60 mm x 63.50 mm)
• Rear	17 in. x 4.50 in. (431.80 mm x 114.30 mm)
Brakes:	
• Caliper Type	4-piston fixed front, and 2-piston torque-free floating rear
• Rotor Type (diameter x width):	Patented, uniform expansion rotors (floating, front only)
• Front (floating)	11.80 in. x .20 in. (299.72 mm x 5.08 mm)
• Rear	11.50 in. x .23 in. (292.10 mm x 5.84 mm)
Suspension Travel:	
• Front Wheel	5 in. (127 mm)
• Rear Wheel	3.10 in. (78.74 mm)

PERFORMANCE

Engine Torque (per SAE J1349):	
• North America	92 ft. lbs. @ 3000 rpm (124.75 Nm @ 3000 rpm)
Lean Angle (per SAE J1168):	
• Right	31.8°
• Left	32°
Fuel Economy (EPA urban/highway test)	35/54 mpg (6.72/4.36 L/100 km)

ELECTRIC

Battery (per Battery Council International Rating)	Sealed, maintenance-free, 12V, 19-amp/hour, 270 cca
Charging	Three-phase, 40-amp system (493W @ 13.5V, 2000 rpm, 540W max power @ 13.5V)
Starting	1.2 kW electric with solenoid shift starter motor engagement

Lights (as per country regulation):

• Headlamp (quartz halogen)	55-watt low beam, 60-watt high beam
• Tail/Stop Lights	8W/28W (5W/21W)
• Turn Signal Lights	28W (21W) self-canceling
• Indicator Lamps	High beam, directional light bar, neutral, low oil pressure, engine diagnostics, turn signals, security system ⁷ (optional), 6-speed, low fuel warnings

Electric Power Outlet Standard

WARRANTY

Warranty ⁸	24 months (unlimited mileage)
Service Interval	First 1,000 miles (1,600 km), every 5,000 miles (8,000 km) thereafter

¹ Vehicles depicted may differ from vehicles manufactured and delivered. Specifications and prices listed may differ from specifications and prices of vehicles manufactured and delivered. All product descriptions (including depictions, specifications, dimensions, measurements, ratings and competitive comparisons) are based on available information at the time of publication. Although such descriptions are believed correct, errors and changes can occur and complete accuracy cannot be guaranteed. Harley-Davidson may make changes at any time to prices and specifications, and may change or discontinue models, without notice and without incurring any obligation. Attention: Vehicles in the configurations shown and many of the accessories described in this catalog may not be available for sale or use in some locations. Please check with your dealer for complete product details and the latest information. All models feature 6-speed transmission (VRSC™ models and Sportster® models are 5-speed) and carbon fiber belt final drive; multi-plate clutch with diaphragm spring in oil bath; and 2-year unlimited mileage warranty.

² Measurement reflects **180 lb.** (81.7 kg) operator weight.

³ Primary case oil fill is 32 oz. or as needed to fill to bottom of diaphragm.

⁴ Recommended 91 octane or higher fuel (R+M)/2.

⁵ Standard and optional fuel systems may vary by country and region.

⁶ U.S. and HDI markets, except Japan: Belt, 32/64 ratio.

⁷ Standard and optional wheels may vary by country and region.

⁸ North America security system includes immobilizer; outside North America the security system includes immobilizer and siren.

⁹ See motorcycle owner's manual for complete details.