

# FLHR ROAD KING®

## 2010 FACTS & FEATURES



### MODEL HIGHLIGHTS

**NEW** Helical cut 5th gear for improved transmission sound

- Black powder-coated powertrain with chrome covers
- Chrome 2-1-2 dual exhaust with tapered mufflers
- Black, 28-spoke Cast Aluminum wheels with narrow whitewall tires
- Chrome, low profile fuel tank console with electronic speedometer
- Clean rear fender and low-mounted license plate module with LED illumination
- Deep FL front fender with trim
- Stainless steel, ergonomic handlebar
- One-piece, two-up Road King® seat
- Clear, large Lexan® quick-release detachable windshield
- Injection-molded hard saddlebags, 2.26 cu. ft. volume
- Large Hiawatha headlight and chrome nacelle
- Auxiliary passing lights

### KEY FEATURES

The Road King® combines Harley-Davidson styling heritage with long-range riding comfort. The detachable windshield and hard-shell saddlebags make this a versatile motorcycle suitable for touring or commuting.

The innovative Harley-Davidson® Touring chassis is based on a single-spar, rigid backbone frame and a stout swingarm developed to withstand the demands of long-haul touring riders and today's more-powerful engines.

- Rubber-mounted Twin Cam 96™ V-Twin engine with Electronic Sequential Port Fuel Injection (ESPFI) with heated O2 sensors and Electronic Throttle Control (ETC)
- 6-Speed Cruise Drive® transmission with integrated Isolated Drive System (IDS)
- Dunlop® "Multi-Tread" rear tire construction extends tire life by 25 percent
- Brembo® 4-piston front and rear caliper with dual front rotor brake system
- Air-adjustable rear shocks
- Full-length rider footboards
- Height-adjustable passenger footboards
- Six-gallon fuel tank
- Optional Anti-lock Braking System (ABS)
- Optional electronic cruise control
- Optional Harley-Davidson® Smart Security System with hands-free security fob
- Optional Chrome, Profile Laced Aluminum wheels

### SPECIFICATIONS\*

#### DIMENSIONS

Length (in./mm)	95.0/2413.0
Seat Height (laden) (in./mm)	27.30/693.42
Wheelbase (in./mm)	63.50/1612.90
Tire	Dunlop® Harley-Davidson® Series, bias narrow whitewall
• Front	D408F NW 130/80B17 65H
• Rear	D407 NW 180/65B16 81H
Wheel	
• Front	Black, 28-spoke Cast Aluminum 17 in. x 3 in. (431.80 mm x 76.20 mm)
• Rear	Black, 28-spoke Cast Aluminum 16 in. x 5 in. (406.40 mm x 127.0 mm)
• Optional Style	Chrome, Profile Laced Aluminum

Fuel Capacity (U.S. gals./liters) 6.0/22.71

Weight as Shipped (lbs./kg) 775.0/351.54

#### POWERTRAIN

Engine	Air-cooled, Twin Cam 96™
Displacement (in./cc)	96.0/1584
Fuel System	Electronic Sequential Port Fuel Injection (ESPFI)
Transmission	6-Speed Cruise Drive®
Miles Per Gallon	54.0 HWY/35.0 CITY

#### COLOR OPTIONS

Solids	<ul style="list-style-type: none"> <li>• Vivid Black</li> <li>• Flame Blue Pearl</li> <li>• Red Hot Sunglo</li> </ul>
Two-Tones	<ul style="list-style-type: none"> <li>• Scarlet Red/Vivid Black</li> <li>• Flame Blue Pearl/Brilliant Silver Pearl</li> </ul>

#### U.S. MSRP

Vivid Black	\$16,999
Solids	\$17,399
Two-Tones	\$17,769

\*For additional specifications and information go to [www.h-dmedia.com](http://www.h-dmedia.com)