

VRSCDX

NIGHT ROD® SPECIAL

MODEL SPECIFICATIONS¹



DIMENSIONS	
Length	94.4 in. (2398 mm)
Overall Width	34.6 in. (879 mm)
Overall Height	45.5 in. (1156 mm)
Seat Height:	
• Laden ²	25.2 in. (640 mm)
• Unladen	26.3 in. (668 mm)
Ground Clearance	4.2 in. (107 mm)
Rake <i>(steering head)</i>	34°
Fork Angle	36°
Trail	4.5 in. (114 mm)
Wheelbase	67.2 in. (1707 mm)
Tires <i>(Michelin® Scorcher™ "11" front and rear):</i>	
• Front – Scorcher™ "11" 120/70ZR-19 60W	
• Rear – Scorcher™ "11" 240/40R-18 79V	
Fuel Capacity	5.0 gal. (18.9 L)
<i>(warning light at approximately 0.5 gal.)</i>	
Oil Capacity <i>(w/filter)</i>	5.0 qts. (4.7 L)
Coolant Capacity	2.5 qts. (2.4 L)
Weight:	
• As Shipped	643 lbs. (292.0 kg)
• In Running Order	676 lbs. (307.0 kg)
• Gross Vehicle Weight Rating	1075 lbs. (488.0 kg)
• Gross Axle Weight Rating	
• Front	377 lbs. (171.0 kg)
• Rear	698 lbs. (317.0 kg)
ENGINE	
Engine ³	Liquid-cooled, Revolution®, 60° V-Twin
Valves	Overhead cam, 4 valves per cylinder, solid tappet with shim-under-bucket lash adjustment
Bore x Stroke	4.134 in. x 2.835 in. (105 mm x 72 mm)
Displacement	76.28 cu. in. (1250 cc)
Compression Ratio	11.5:1
Fuel System ³	Electronic Sequential Port Fuel Injection (ESPFI)
Air Cleaner	Down draft intake
Lubrication System	Wet-sump, integrated with powertrain crankcase

DRIVETRAIN	
Primary Drive	Gear, 117/64 ratio
Final Drive	Belt, 72/28 ratio
Clutch	9-plate, wet, A&S (Assist & Slip)
Transmission	5-speed
Gear Ratios (overall):	U.S.
• 1st	11.752
• 2nd	7.898
• 3rd	6.322
• 4th	5.459
• 5th	4.899
CHASSIS	
Frame	Steel perimeter upper frame with hydroformed main rails and bolt-on lower frame rails; MIG welded
Swingarm	Polished, one-piece cast aluminum with black powder-coat finish
Front Forks	Wide, 49 mm custom
Rear Shocks	Preload adjustable
Wheels:	Black, Slotted Disc Cast Aluminum
• Front	19 in. x 3 in. (483 mm x 76 mm)
• Rear	18 in. x 8 in. (457 mm x 203 mm)
Brakes:	
• Caliper Type	4-piston front and rear
• Rotor Type	Patented, one-piece floating rotor <i>(front)</i> , uniform expansion rotor <i>(rear)</i>
<i>(diameter x width):</i>	
• Front <i>(dual)</i>	11.81 in. x .2 in. (300 mm x 5 mm)
• Rear	11.81 in. x .28 in. (300 mm x 7 mm)
• ABS Option	Available
Suspension Travel:	
• Front	4 in. (102 mm)
• Rear	2.9 in. (74 mm)
PERFORMANCE	
Engine Torque ⁵ <i>(per SAE J1349):</i>	
• North America	85 ft. lbs. @ 7000 RPM (115 Nm @ 7000 RPM)
Lean Angle <i>(per SAE J1168):</i>	
• Right	32°
• Left	32°
Fuel Economy ⁶	34/42 mpg (6.92/5.60 L/100 km)
<i>(EPA urban/highway test)</i>	

ELECTRIC	
Battery <i>(per Battery Council International Rating)</i>	Sealed, maintenance-free, 12V, 19-amp/hour, 270 cca
Charging	Three-Phase, 38-amp system <i>(439W @ 13V, 2000 RPM, 489W max power @ 13V)</i>
Starting	0.08 kW electric with direct drive starter motor engagement
Lights <i>(as per country regulation):</i>	
• Headlamp <i>(quartz halogen)</i>	55-watt low beam, 60-watt high beam
• Tail/Stop Lights	8W/28W reflector optics (5W/21W)
• Turn Signal Lights	28W (21W) self-canceling
• Indicator Lamps	High beam, neutral, low oil pressure, turn signals, engine diagnostics, security system ⁷ <i>(optional)</i> , coolant temperature, low fuel warnings
WARRANTY	
Warranty ⁸	24 months <i>(unlimited mileage)</i>
Service Interval	First 1,000 miles (1,600 km), every 5,000 miles (8,000 km) thereafter

¹ Vehicles depicted may differ from vehicles manufactured and delivered. Specifications and prices listed may differ from specifications and prices of vehicles manufactured and delivered. All product descriptions (including depictions, specifications, dimensions, measurements, ratings and competitive comparisons) are based on available information at the time of publication. Although such descriptions are believed correct, errors and changes can occur and complete accuracy cannot be guaranteed. Harley-Davidson may make changes at any time to prices and specifications, and may change or discontinue models, without notice and without incurring any obligation. Attention: Vehicles in the configurations shown and many of the accessories described in this catalog may not be available for sale or use in some locations. Please check with your dealer for complete product details and the latest information. All models feature 6-speed transmission (VRSC™ models and Sportster® models are 5-speed) and carbon fiber belt final drive; multi-plate clutch with diaphragm spring in oil bath; and 2-year unlimited mileage warranty.

² Measurement reflects **180 lb.** (81.7 kg) operator weight.

³ Recommended 91 octane or higher fuel (R+M)/2.

⁴ Standard and optional wheels may vary by country and region.

⁵ Values shown are nominal. Performance may vary by country and region.

⁶ Estimated from fuel economy tests on a sample motorcycle from the corresponding family conducted by Harley-Davidson under ideal laboratory conditions. Not all motorcycle models undergo fuel economy testing. Fuel economy and mileage may vary among motorcycle models within a family. Your mileage may vary depending on your personal riding habits, weather conditions, trip length, vehicle condition and vehicle configuration and other conditions. Break-in mileage may vary.

⁷ North America security system includes immobilizer; outside North America the security system includes immobilizer and siren.

⁸ See motorcycle owner's manual for complete details.