

SuperLow®

2014 FACTS & FEATURES



MODEL HIGHLIGHTS

NEW Paint color options and graphics

NEW Front and rear brakes with a larger front rotor, more-rigid front and rear calipers with larger pistons, and braided stainless steel brake lines

NEW Optional Anti-lock Braking System (ABS)

NEW Trip switch function allows odometer to display gear indicator and RPMs

NEW Optional keyless H-D® Factory Security System with a proximity-based, hands-free security fob

NEW Integrated electrical system including new hand controls, speedometer, updated wire harness, oil tank, and side covers

- Black side covers to match bodywork finish
- Black, Split 5-Spoke wheels with machined rims
- Wheel size: front 18 x 3.5 inches, rear 17 x 4.5 inches
- Michelin® Scorchers® 11 radial tires: Front 120/70ZR18; rear 150/60ZR17
- Front end geometry contributes to confident handling
- 68/29 (2.34:1) final drive ratio for smooth acceleration
- 4.5-gallon fuel tank for extended range
- Solo seat with deep bucket shape is easy to straddle, seat height is 25.5 inches
- Easy-reach handlebar
- Revised rear suspension with 2.5 inches wheel travel for added comfort
- Silver, powder-coated engine with polished covers
- Chrome exhaust with dual staggered shorty mufflers
- Full-coverage rear fender with painted supports
- Sport front fender
- Polished headlamp visor

KEY FEATURES

The SuperLow® model is easy to own and fun to ride. Balanced and responsive handling help rider and machine glide through corners with smooth confidence. The combination of wheel size, radial tires and front-end geometry contribute to outstanding maneuverability. The final drive ratio is matched to the rear wheel size to provide smooth acceleration.

Generous rear-suspension travel, a deeply cushioned seat and easy-reach handlebar offer outstanding comfort. A low seat height, the broad V-Twin powerband and clean styling complete a package that will make the SuperLow® appealing to many riders.

- Evolution® V-Twin powertrain with Electronic Sequential Port Fuel Injection (ESPFI)
- Rubber-mounted powertrain to reduce vibration
- 5-speed Transmission
- Dual staggered exhaust
- Disc brakes
- Mid-mounted foot controls
- Handlebar-mounted electronic speedometer

SPECIFICATIONS*

DIMENSIONS

Length (in./mm)	87.2/2215
Seat Height (laden) (in./mm)	25.5/648
Wheelbase (in./mm)	59.1/1500
Tire	Michelin® Scorchers® "11" front and rear
• Front	Scorchers® "11F" 120/70 ZR-18 59W
• Rear	Scorchers® "11" 150/60 ZR-17 66W
Wheel	
• Front	Black, Split 5-spoke with Machined Rim 18 in. x 3.5 in. (457 mm x 89 mm)
• Rear	Black, Split 5-Spoke with Machined Rim 17 in. x 4.5 in. (432 mm x 114 mm)
Fuel Capacity (U.S. gals./liters)	4.5/17
Weight as Shipped (lbs./kg)	540/245

POWERTRAIN

Engine	Air-cooled, Evolution®
Displacement (in./cc)	53.9/883
Fuel System	Electronic Sequential Port Fuel Injection (ESPFI)
Transmission	5-speed
Miles Per Gallon	51 MPG combined City/Hwy

COLOR OPTIONS

Solids	<ul style="list-style-type: none"> • Vivid Black • Brilliant Silver
Two-Tones	<ul style="list-style-type: none"> • Mysterious Red Sunglo/Blackened Cayenne Sunglo • Amber Whiskey/Brilliant Silver

U.S. MSRP

Vivid Black	\$8,249
Solids	\$8,564
Two-Tones	\$8,774

*For additional specifications and information go to www.harley-davidson.com