

# FLHTKSE CVO™ LIMITED

## MODEL SPECIFICATIONS¹



DIMENSIONS	
Length	<b>102.4 in.</b> (2600 mm)
Overall Width	<b>42.9 in.</b> (1090 mm)
Overall Height	<b>56.7 in.</b> (1440 mm)
Seat Height:	
• Laden²	<b>28.4 in.</b> (720 mm)
• Unladen	<b>29.1 in.</b> (740 mm)
Ground Clearance	<b>5.3 in.</b> (135 mm)
Rake (steering head)	26°
Fork Angle	29.25°
Trail	<b>6.7 in.</b> (170 mm)
Wheelbase	<b>64 in.</b> (1625 mm)
Tires (Dunlop® Harley-Davidson® Series, bias blackwall front and rear):	
• Front – D408F	BW 130/80B17 65H
• Rear – D407T	BW 180/65B16 81H
Fuel Capacity	<b>6 gal.</b> (22.7 L)
(warning light at approximately 1.0 gal.)	
Oil Capacity (w/filter)	<b>4 qts.</b> (3.8 L)
Transmission Capacity	<b>1 qt.</b> (.95 L)
Primary Chain	<b>1.4 qt.</b> (1.3 L)
Case Capacity	
Coolant Capacity	<b>1.1 qt.</b> (1.04 L)
Weight:	
• As Shipped	<b>909 lbs.</b> (412 kg)
• In Running Order	<b>944 lbs.</b> (428 kg)
• Gross Vehicle Weight Rating	<b>1360 lbs.</b> (617 kg)
• Gross Axle Weight Rating:	
• Front	<b>500 lbs.</b> (227 kg)
• Rear	<b>927 lbs.</b> (420 kg)
Luggage Capacity -Volume	<b>4.7 cu. ft.</b> (0.132 m³)
ENGINE	
Engine	Twin-Cooled™ Twin Cam 110™
Valves	Pushrod-operated, overhead valves with hydraulic, self-adjusting lifters; two valves per cylinder
Bore x Stroke	<b>4 in. x 4.374 in.</b> (101.6 mm x 111.1 mm)
Displacement	<b>110 cu. in.</b> (1801 cc)
Compression Ratio	9.2:1
Fuel System³	Electronic Sequential Port Fuel Injection (ESPFI)
Air Cleaner	Ventilator intake with chrome cover, fiberglass media, washable exposed element with rain sock
Lubrication System	Pressurized, dry-sump

DRIVETRAIN	
Primary Drive	Chain, 34/46 ratio
Final Drive	Belt, 32/68 ratio
Clutch	Hydraulically actuated multi-plate, wet Assist & Slip
Transmission	6-speed Cruise Drive®
Gear Ratios (overall):	<b>U.S.</b>
• 1st	<b>9.593</b>
• 2nd	<b>6.65</b>
• 3rd	<b>4.938</b>
• 4th	<b>4</b>
• 5th	<b>3.407</b>
• 6th	<b>2.875</b>
CHASSIS	
Frame	Mild steel; tubular frame; two-piece stamped and welded backbone; cast and forged junctions; twin downtubes; bolt-on rear frame with forged fender supports; MIG welded
Swingarm	Mild steel; two-piece drawn and welded section; forged junctions; MIG welded
Front Forks	49 mm telescopic, triple-circuit damping
Rear Shocks	Air-adjustable full travel air ride rear suspension
Wheels⁴:	Mirror Chrome Slicer Custom
• Front	<b>17 in. x 3 in.</b> (432 mm x 76 mm)
• Rear	<b>16 in. x 5 in.</b> (406 mm x 127 mm)
Brakes:	
• Caliper Type	32 mm, 4-piston fixed front and rear
• Rotor Type (diameter x width):	Dual floating rotors (front), fixed rotor (rear)
• Front (dual)	<b>11.81 in. x .2 in.</b> (300 mm x 5.1 mm)
• Rear	<b>11.81 in. x .28 in.</b> (300 mm x 7.1 mm)
• Anti-lock Braking System	Standard
Suspension Travel:	
• Front Wheel	<b>4.6 in.</b> (117 mm)
• Rear Wheel	<b>3 in.</b> (76 mm)
PERFORMANCE	
Engine Torque⁵ (per J1349):	
• North America	<b>115.1 ft. lbs. @ 3750 RPM</b> (156 Nm @ 3750 RPM)
Lean Angle (per J1168):	
• Right	34.3°
• Left	33.4°
Fuel Economy⁶ (EPA urban/highway test)	<b>41 mpg</b> (5.7 L/100 km)

ELECTRIC	
Battery (per Battery Council International Rating)	Sealed, maintenance-free, 12V, 28-amp/hour, 405 cca
Charging	Three-phase, 53-amp system (617W @ 13V, 2000 RPM, 690W max power @ 13V)
Starting	1.2 kW electric with solenoid shift starter motor engagement
Lights (as per country regulation):	
• Headlamp: LED 34-watt, 916 lumen low beam, 37-watt, 917 lumen high beam with switchable 20-watt, 1,220 lumen LED fog lamps. Total of 2,136 lumen output at low beam with fog lights.	
• Tail/Stop Lights	LED
• Turn Signal Lights	Tour-Pak® mounted LED and 28W self-canceling
• Rear Tail/Stop/Turn Signal Lights	Tour-Pak® mounted LED stop/turn/tail light bar
• Front Signal Lights	8W/28W
• Indicator Lamps: High beam, running lights, front fender running lights, directional lights, neutral, low oil pressure, engine diagnostics, accessory, speakers, turn signals, security system⁷, gear indication, battery, low fuel warning, cruise control, ABS, miles to empty display, fog/aux lamp indicator	
• Auxiliary Lamps (except where prohibited by law)	Two LED @ 20W each
Electric Power Outlet	Electric power accessory port in fairing and Tour-Pak®
GPS System	New Boom!™ Box 6.5GT audio system with GPS and touchscreen
WARRANTY	
Warranty⁸	24 months (unlimited mileage)
Service Interval⁹	First <b>1000 miles</b> (1600 km), every <b>5000 miles</b> (8000 km) thereafter

¹ Vehicles depicted may differ from vehicles manufactured and delivered. Specifications and prices listed may differ from specifications and prices of vehicles manufactured and delivered. All product descriptions (including depictions, specifications, dimensions, measurements, ratings and competitive comparisons) are based on available information at the time of publication. Although such descriptions are believed correct, errors and changes can occur and complete accuracy cannot be guaranteed. Harley-Davidson may make changes at any time to prices and specifications, and may change or discontinue models, without notice and without incurring any obligation. Attention: Vehicles in the configurations shown and many of the accessories described in this catalog may not be available for sale or use in some locations. Please check with your dealer for complete product details and the latest information. All models feature 6-speed transmission (V-Rod® models and Sportster® models are 5-speed) and carbon fiber belt final drive; multi-plate clutch with diaphragm spring in oil bath; and 2-year unlimited mileage warranty.

² Measurement reflects **180 lb.** (81.7 kg) operator weight.

³ Recommended 91 octane or higher fuel (R+M)/2.

⁴ Standard and optional wheels may vary by country and region.

⁵ Values shown are nominal. Performance may vary by country and region.

⁶ The combined fuel economy numbers were derived using a combination of estimated city and highway values. Fuel economy estimates are derived from US EPA exhaust emission certification data on a sample motorcycle from the corresponding family under ideal laboratory conditions. Your actual fuel economy will vary depending on your personal riding habits, road and driving conditions, vehicle condition and maintenance, tire pressure, vehicle configuration (parts and accessories), and vehicle loading (cargo, rider and passenger weight). Break-in mileage may vary.

⁷ North America security system includes immobilizer; outside North America the security system includes immobilizer and siren.

⁸ See motorcycle owner's manual for complete details.

⁹ Inspections of certain systems and components are required at 2,500 mile (4,000 km) intervals. See Owner's Manual for full details.

# FLTRUSE

## CVO™ ROAD GLIDE® ULTRA

### MODEL SPECIFICATIONS¹



DIMENSIONS	
Length	<b>102.2 in.</b> (2595 mm)
Overall Width	<b>42.2 in.</b> (1070 mm)
Overall Height	<b>55.4 in.</b> (1420 mm)
Seat Height:	
• Laden²	<b>28.4 in.</b> (699 mm)
• Unladen	<b>29.7 in.</b> (755 mm)
Ground Clearance	<b>4.7 in.</b> (120 mm)
Rake (steering head)	26°
Fork Angle	29.3°
Trail	<b>6.7 in.</b> (170 mm)
Wheelbase	<b>64 in.</b> (1625 mm)
Tires (Dunlop® Harley-Davidson® Series, bias blackwall front and rear):	
• Front – D408F	BW 130/80B17 65H
• Rear – D407T	BW 180/65B16 81H
Fuel Capacity	<b>6 gal.</b> (22.7 L)
(warning light at approximately 1.0 gal.)	
Oil Capacity (w/filter)	<b>4 qts.</b> (3.8 L)
Transmission Capacity	<b>1 qt.</b> (.95 L)
Primary Chain	<b>1.4 qts.</b> (1.3 L)
Case Capacity	
Weight:	
• As Shipped	<b>905 lbs.</b> (411 kg)
• In Running Order	<b>943 lbs.</b> (428 kg)
• Gross Vehicle Weight Rating	<b>1360 lbs.</b> (617 kg)
• Gross Axle Weight Rating:	
• Front	<b>500 lbs.</b> (227 kg)
• Rear	<b>927 lbs.</b> (420 kg)
Luggage Capacity - Volume	<b>4.7 cu. ft.</b> (0.132 m³)
ENGINE	
Engine	Twin-Cooled™, Twin Cam 110™
Valves	Pushrod-operated, overhead valves with hydraulic, self-adjusting lifters; two valves per cylinder
Bore x Stroke	<b>4 in. x 4.374 in.</b> (101.6 mm x 111.1 mm)
Displacement	<b>109.9 cu. in.</b> (1801 cc)
Compression Ratio	9.2:1
Fuel System³	Electronic Sequential Port Fuel Injection (ESPFI)
Air Cleaner	Ventilator Intake with chrome cover, fiberglass media, washable exposed element with rain sock
Lubrication System	Pressurized, dry-sump

DRIVETRAIN	
Primary Drive	Chain, 34/46 ratio
Final Drive	Belt, 32/68 ratio
Clutch	Hydraulically actuated, 9-plate wet, with high performance spring
Transmission	6-Speed Cruise Drive®
Gear Ratios (overall):	<b>U.S.</b>
• 1st	<b>9.593</b>
• 2nd	<b>6.65</b>
• 3rd	<b>4.938</b>
• 4th	<b>4</b>
• 5th	<b>3.407</b>
• 6th	<b>2.875</b>
CHASSIS	
Frame	Mild steel; tubular frame, two-piece stamped and welded backbone; cast and forged junctions; twin down tubes; bolt-on rear frame with forged fender supports; MIG welded
Swingarm	Mild steel, two piece drawn and welded section; forged junctions; MIG welded
Front Forks	49 mm telescopic, triple-circuit damping
Rear Shocks	Air-adjustable full travel air ride rear suspension
Wheels⁴:	Mirror Chrome Slicer Custom Wheel
• Front	<b>17 in. x 3 in.</b> (432 mm x 76 mm)
• Rear	<b>16 in. x 5 in.</b> (406 mm x 127 mm)
Brakes:	
• Caliper Type	32 mm, 4-piston fixed front and rear
• Rotor Type (diameter x width):	Dual floating rotors (front), fixed rotor (rear)
• Front (dual)	<b>11.81 in. x .2 in.</b> (300 mm x 5.1 mm)
• Rear	<b>11.81 in. x .28 in.</b> (300 mm x 7.1 mm)
• Anti-lock Braking System	Standard
Suspension Travel:	
• Front Wheel	<b>4.6 in.</b> (117 mm)
• Rear Wheel	<b>3 in.</b> (76 mm)
PERFORMANCE	
Engine Torque⁵ (per J1349):	
• North America	<b>115.1 ft. lbs. @ 3750 RPM</b> (156 Nm @ 3750 RPM)
Lean Angle (per J1168):	
• Right	31.9°
• Left	31.8°
Fuel Economy⁶ (EPA urban/highway test)	<b>41 mpg</b> (5.7 L/100 km)

ELECTRIC	
Battery (per Battery Council International Rating)	Sealed, maintenance-free, 12V, 28-amp/hour, 405 cca
Charging	Three-phase, 50-amp system (617W @ 13V, 2000 RPM, 690W max power @ 13V)
Starting	1.2 kW electric with solenoid shift starter motor engagement
Lights (as per country regulation):	
• Headlamp	LED 40-watt, 1060 lumen low beam, 60-watt, 1560 lumen high beam
• Tail/Stop Lights	LED
• Turn Signal Lights	Tour-Pak® mounted LED and 28W self-cancelling
• Indicator Lamps	High beam, neutral, running lights, turn signals, low oil pressure, engine diagnostics, cruise control, speakers, accessory, security system¹, 6-speed, low fuel warning, ABS
Electric Power Outlet	Electric power accessory port in fairing and Tour-Pak®
GPS System	New Boom!™ Box 6.5GT audio system with GPS and touchscreen
WARRANTY	
Warranty⁷	24 months (unlimited mileage)
Service Interval⁸	First <b>1000 miles</b> (1600 km), every <b>5000 miles</b> (8000 km) thereafter

¹ Vehicles depicted may differ from vehicles manufactured and delivered. Specifications and prices listed may differ from specifications and prices of vehicles manufactured and delivered. All product descriptions (including depictions, specifications, dimensions, measurements, ratings and competitive comparisons) are based on available information at the time of publication. Although such descriptions are believed correct, errors and changes can occur and complete accuracy cannot be guaranteed. Harley-Davidson may make changes at any time to prices and specifications, and may change or discontinue models, without notice and without incurring any obligation. Attention: Vehicles in the configurations shown and many of the accessories described in this catalog may not be available for sale or use in some locations. Please check with your dealer for complete product details and the latest information. All models feature 6-speed transmission (V-Rod® models and Sportster® models are 5-speed) and carbon fiber belt final drive; multi-plate clutch with diaphragm spring in oil bath; and 2-year unlimited mileage warranty.

² Measurement reflects **180 lb.** (81.7 kg) operator weight.

³ Recommended 91 octane or higher fuel (R+M)/2.

⁴ Standard and optional wheels may vary by country and region.

⁵ Values shown are nominal. Performance may vary by country and region.

⁶ The combined fuel economy numbers were derived using a combination of estimated city and highway values. Fuel economy estimates are derived from US EPA exhaust emission certification data on a sample motorcycle from the corresponding family under ideal laboratory conditions. Your actual fuel economy will vary depending on your personal riding habits, road and driving conditions, vehicle condition and maintenance, tire pressure, vehicle configuration (parts and accessories), and vehicle loading (cargo, rider and passenger weight). Break-in mileage may vary.

⁷ North America security system includes immobilizer; outside North America the security system includes immobilizer and siren.

⁸ See motorcycle owner's manual for complete details.

⁹ Inspections of certain systems and components are required at 2,500 mile (4,000 km) intervals. See Owner's Manual for full details.

# FLHXSE CVO™ STREET GLIDE®

## MODEL SPECIFICATIONS¹



DIMENSIONS	
Length	<b>96.7 in.</b> (2455 mm)
Overall Width	<b>38.2 in.</b> (970 mm)
Overall Height	<b>53 in.</b> (1345 mm)
Seat Height:	
• Laden²	<b>26.3 in.</b> (668 mm)
• Unladen	<b>27.2 in.</b> (690 mm)
Ground Clearance	<b>4.9 in.</b> (125 mm)
Rake (steering head)	26°
Fork Angle	29.25°
Trail	<b>6.7 in.</b> (170 mm)
Wheelbase	<b>64 in.</b> (1625 mm)
Tires (Dunlop® Harley-Davidson® Series, bias blackwall front and radial blackwall rear):	
• Front – D408F	130/60B19 61H
• Rear – D407	180/55B18 80H
Fuel Capacity	<b>6.0 gal.</b> (22.7 L)
(warning light at approximately 1.0 gal.)	
Oil Capacity (w/filter)	<b>4.0 qts.</b> (3.8 L)
Transmission Capacity	<b>1 qt.</b> (.95 L)
Primary Chain Case Capacity	<b>1.4 qt.</b> (1.3 L)
Coolant Capacity	<b>1.1 qt.</b> (1.04 L)
Weight:	
• As Shipped	<b>836 lbs.</b> (379 kg)
• In Running Order	<b>870 lbs.</b> (395 kg)
• Gross Vehicle Weight Rating	<b>1360 lbs.</b> (617 kg)
• Gross Axle Weight Rating:	
• Front	<b>500 lbs.</b> (227 kg)
• Rear	<b>927 lbs.</b> (420 kg)
Luggage Capacity	<b>2.4 cu. ft.</b> (0.068 m³)
• Volume	
ENGINE	
Engine	Twin-Cooled™ Twin Cam 110™
Valves	Pushrod-operated, overhead valves with hydraulic, self-adjusting lifters; two valves per cylinder
Bore x Stroke	<b>4 in. x 4.375 in.</b> (101.6 mm x 111.1 mm)
Displacement	<b>109.9 cu. in.</b> (1801 cc)
Compression Ratio	9.2:1
Fuel System³	Electronic Sequential Port Fuel Injection (ESPFI)
Air Cleaner	Ventilator intake with cosmetic cover, fiberglass media, washable exposed element with rain sock
Lubrication System	Pressurized, dry-sump

DRIVETRAIN	
Primary Drive	Chain, 34/46 ratio
Final Drive	Belt, 32/68 ratio
Clutch	Hydraulically actuated multi-plate, wet Assist & Slip
Transmission	6-Speed Cruise Drive®
Gear Ratios (overall):	<b>U.S.</b>
• 1st	<b>9.593</b>
• 2nd	<b>6.65</b>
• 3rd	<b>4.938</b>
• 4th	<b>4</b>
• 5th	<b>3.407</b>
• 6th	<b>2.875</b>
CHASSIS	
Frame	Mild steel; tubular frame, two-piece stamped and welded backbone; cast and forged junctions; twin down tubes; bolt-on rear frame with forged fender supports; MIG welded
Swingarm	Mild steel, two piece drawn and welded section; forged junctions; MIG welded
Front Forks	49 mm telescopic, triple-circuit damping
Rear Shocks	Premium Low Hand-Adjustable Rear Suspension
Wheels⁴:	Mirror Chrome Aggressor Custom Wheel
• Front	<b>19 in. x 3.5 in.</b> (483 mm x 89 mm)
• Rear	<b>18 in. x 5 in.</b> (457 mm x 127 mm)
Brakes:	
• Caliper Type	32 mm, 4-piston fixed front and rear
• Rotor Type (diameter x width):	Dual floating rotors (front), fixed rotor (rear)
• Front	<b>11.81 in. x .2 in.</b> (300 mm x 5.1 mm)
• Rear	<b>11.81 in. x .28 in.</b> (300 mm x 7.1 mm)
• Anti-lock Braking System	Standard
Suspension Travel:	
• Front Wheel	<b>4.6 in.</b> (117 mm)
• Rear Wheel	<b>2.15 in.</b> (54.6 mm)
PERFORMANCE	
Engine Torque⁵ (per J1349):	
• North America	<b>115.1 ft. lbs. @ 3750 RPM</b> (156 Nm @ 3750 RPM)
Lean Angle (per J1168):	
• Right	32°
• Left	31°
Fuel Economy⁶ (EPA urban/highway test)	<b>41 mpg</b> (5.7 L/100 km)

ELECTRIC	
Battery (per Battery Council International Rating)	Sealed, maintenance-free, 12V, 28-amp/hour, 405 cca
Charging	Three-phase, 53-amp system (617W @ 13V, 2000 RPM, 690W max power @ 13V)
Starting	1.2kW electric with solenoid shift starter motor engagement
Lights (as per country regulation):	
• Headlamp	LED 34-watt, 916 lumen low beam, 37-watt, 917 lumen high beam
• Rear Tail/Stop/Turn Signal Lights	8W/28W self-canceling
• Tail/Stop Lights	LED
• Turn Signal Lights	11W self-canceling
• Rear Tail/Stop/Turn Signal Lights	LED
• Front Signal Lights	8W/28W
• Indicator Lamps	High beam, running lights, directional lights, neutral, low oil pressure, engine diagnostics, accessory, speakers, turn signals, security system⁷, gear indication, battery, low fuel warning, cruise control, ABS, miles to empty display, fog/aux lamp indicator
WARRANTY	
Warranty⁸	24 months (unlimited mileage)
Service Interval⁹	First <b>1000 miles</b> (1600 km), every <b>5000 miles</b> (8000 km) thereafter

¹ Vehicles depicted may differ from vehicles manufactured and delivered. Specifications and prices listed may differ from specifications and prices of vehicles manufactured and delivered. All product descriptions (including depictions, specifications, dimensions, measurements, ratings and competitive comparisons) are based on available information at the time of publication. Although such descriptions are believed correct, errors and changes can occur and complete accuracy cannot be guaranteed. Harley-Davidson may make changes at any time to prices and specifications, and may change or discontinue models, without notice and without incurring any obligation. Attention: Vehicles in the configurations shown and many of the accessories described in this catalog may not be available for sale or use in some locations. Please check with your dealer for complete product details and the latest information. All models feature 6-speed transmission (V-Rod® models and Sportster® models are 5-speed) and carbon fiber belt final drive; multi-plate clutch with diaphragm spring in oil bath; and 2-year unlimited mileage warranty.

² Measurement reflects **180 lb.** (81.7 kg) operator weight.

³ Recommended 91 octane or higher fuel (R+M)/2.

⁴ Standard and optional wheels may vary by country and region.

⁵ Values shown are nominal. Performance may vary by country and region.

⁶ The combined fuel economy numbers were derived using a combination of estimated city and highway values. Fuel economy estimates are derived from US EPA exhaust emission certification data on a sample motorcycle from the corresponding family under ideal laboratory conditions. Your actual fuel economy will vary depending on your personal riding habits, road and driving conditions, vehicle condition and maintenance, tire pressure, vehicle configuration (parts and accessories), and vehicle loading (cargo, rider and passenger weight). Break-in mileage may vary.

⁷ North America security system includes immobilizer; outside North America the security system includes immobilizer and siren.

⁸ See motorcycle owner's manual for complete details.

⁹ Inspections of certain systems and components are required at 2,500 mile (4,000 km) intervals. See Owner's Manual for full details.



# FLSTNSE

## CVO™ SOFTAIL® DELUXE

### MODEL SPECIFICATIONS¹



DIMENSIONS	
Length	<b>95.7 in.</b> (2430 mm)
Overall Width	<b>39.2 in.</b> (995 mm)
Overall Height	<b>57.3 in.</b> (1455 mm)
Seat Height:	
• Laden²	<b>24 in.</b> (609.6 mm)
• Unladen	<b>25.8 in.</b> (655 mm)
Ground Clearance	<b>4.7 in.</b> (120 mm)
Rake (steering head)	32.1°
Fork Angle	32°
Trail	<b>5.8 in.</b> (147 mm)
Wheelbase	<b>64.2 in.</b> (1630 mm)
Tires (Dunlop® Harley-Davidson® Series, wide whitewall):	
• Front – D402F WW	MT90B16 M/C 72H
• Rear – D402 WW	MU85B16 77H
Fuel Capacity	<b>5.0 gal.</b> (18.9 L)
(warning light at approximately 1.0 gal.)	
Oil Capacity (w/filter)	<b>3.5 qts.</b> (3.3 L)
Transmission Capacity	<b>1 qt.</b> (.95 L)
Primary Chain Case Capacity	<b>1 qts.</b> (.95 L)
Weight:	
• As Shipped	<b>749 lbs.</b> (340 kg)
• In Running Order	<b>782 lbs.</b> (355 kg)
• Gross Vehicle Weight Rating	<b>1160 lbs.</b> (526 kg)
• Gross Axle Weight Rating:	
• Front	<b>430 lbs.</b> (195 kg)
• Rear	<b>730 lbs.</b> (331 kg)
Luggage Capacity -Volume	<b>1.79 cu. ft.</b> (0.0501 m³)
ENGINE	
Engine	Air-cooled, Twin Cam 110B™
Valves	Pushrod-operated, overhead valves with hydraulic, self-adjusting lifters; two valves per cylinder
Bore x Stroke	<b>4 in. x 4.374 in.</b> (101.6 mm x 111.1 mm)
Displacement	<b>110 cu. in.</b> (1801 cc)
Compression Ratio	9.2:1
Fuel System³	Electronic Sequential Port Fuel Injection (ESPFI)
Air Cleaner	Ventilator intake with chrome cover, fiberglass media, washable exposed element with rain sock
Lubrication System	Pressurized, dry-sump

DRIVETRAIN	
Primary Drive	Chain, 34/46 ratio
Final Drive	Belt, 32/66 ratio
Clutch	Hydraulically actuated, 9-plate wet, with high-performance spring
Transmission	6-speed Cruise Drive®
Gear Ratios (overall):	<b>U.S.</b>
• 1st	<b>9.311</b>
• 2nd	<b>6.454</b>
• 3rd	<b>4.793</b>
• 4th	<b>3.882</b>
• 5th	<b>3.307</b>
• 6th	<b>2.79</b>
CHASSIS	
Frame	Mild steel, tubular frame; rectangular section backbone; stamped, cast and forged junctions; MIG welded; color coordinated with vehicle
Swingarm	Mild steel tube sections; forged junctions; MIG welded; color coordinated with vehicle
Front Forks	41.3 mm telescopic, chrome upper fork-slider covers
Rear Shocks	Hidden, horizontal-mounted, coil-over
Wheels⁴:	Chrome, 9-Spoke Cast Aluminum
• Front	<b>16 in. x 3 in.</b> (406 mm x 76 mm)
• Rear	<b>16 in. x 3 in.</b> (406 mm x 76 mm)
Brakes:	
• Caliper Type	4-piston fixed front; 2-piston floating rear
• Rotor Type	Single floating Turbine™ rotor
(diameter x width):	
• Front	<b>11.81 in. x .2 in.</b> (300 mm x 5.1 mm)
• Rear	<b>11.5 in. x .23 in.</b> (292 mm x 5.8 mm)
• Anti-lock Braking System	Standard
Suspension Travel:	
• Front Wheel	<b>5.1 in.</b> (130 mm)
• Rear Wheel	<b>3.6 in.</b> (91 mm)
PERFORMANCE	
Engine Torque⁵ (per J1349):	
• North America	<b>107.7 ft. lbs. @ 3000 RPM</b> (146 Nm @ 3000 RPM)
Lean Angle (per J1168):	
• Right	25.8°
• Left	27°
Fuel Economy⁶ (EPA urban/highway test)	<b>43 mpg</b> (5.5 L/100 km)

ELECTRIC	
Battery (per Battery Council International Rating)	Sealed, maintenance-free, 12V, 19-amp/hour, 270 cca
Charging	Three-phase, 38-amp system (439W @ 13V, 2000 RPM, 489W max power @ 13V)
Starting	1.2kW electric with solenoid shift starter motor engagement
Lights (as per country regulation):	
• Headlamp	LED 34-watt, 916 lumen low beam, 37-watt, 917 lumen high beam with switchable 20-watt, 1220 lumen, LED Fog Lamps for a total of 2136 lumen output at low beam with fog lights
• Rear Tail/Stop/Turn Signal Lights	28W/21W Incandescent stop/turn/tail signal lights (self cancelling) with red lenses
• Front Signal Lights	Incandescent front turn signals with smoked lenses
• Indicator Lamps	High beam, running lights, neutral, low oil pressure, engine diagnostics, turn signals, security system⁷, 6-speed, low fuel warning, cruise control, ABS
WARRANTY	
Warranty⁸	24 months (unlimited mileage)
Service Interval⁹	First <b>1000 miles</b> (1600 km), every <b>5000 miles</b> (8000 km) thereafter

¹ Vehicles depicted may differ from vehicles manufactured and delivered. Specifications and prices listed may differ from specifications and prices of vehicles manufactured and delivered. All product descriptions (including depictions, specifications, dimensions, measurements, ratings and competitive comparisons) are based on available information at the time of publication. Although such descriptions are believed correct, errors and changes can occur and complete accuracy cannot be guaranteed. Harley-Davidson may make changes at any time to prices and specifications, and may change or discontinue models, without notice and without incurring any obligation. Attention: Vehicles in the configurations shown and many of the accessories described in this catalog may not be available for sale or use in some locations. Please check with your dealer for complete product details and the latest information. All models feature 6-speed transmission (V-Rod® models and Sportster® models are 5-speed) and carbon fiber belt final drive; multi-plate clutch with diaphragm spring in oil bath; and 2-year unlimited mileage warranty.

² Measurement reflects **180 lb.** (81.7 kg) operator weight.

³ Recommended 91 octane or higher fuel (R+M)/2.

⁴ Standard and optional wheels may vary by country and region.

⁵ Values shown are nominal. Performance may vary by country and region.

⁶ The combined fuel economy numbers were derived using a combination of estimated city and highway values. Fuel economy estimates are derived from US EPA exhaust emission certification data on a sample motorcycle from the corresponding family under ideal laboratory conditions. Your actual fuel economy will vary depending on your personal riding habits, road and driving conditions, vehicle condition and maintenance, tire pressure, vehicle configuration (parts and accessories), and vehicle loading (cargo, rider and passenger weight). Break-in mileage may vary.

⁷ North America security system includes immobilizer; outside North America the security system includes immobilizer and siren.

⁸ See motorcycle owner's manual for complete details.

⁹ Inspections of certain systems and components are required at 2,500 mile (4,000 km) intervals. See Owner's Manual for full details.

2015

# CVO™ FAMILY

MANUFACTURER'S SUGGESTED RETAIL PRICE (MSRP)<sup>1</sup>



## FLHTKSE CVO™ LIMITED

<b>MSRP</b> Custom	<b>\$39,349</b>
Anti-lock Braking System Option	STND
Security System Option	STND
Cruise Control Option	STND
Premium Radio Option	STND
California Emissions	\$200
Freight <sup>2</sup>	\$435

## FLSTNSE CVO™ SOFTAIL® DELUXE

<b>MSRP</b> Custom	<b>\$28,999</b>
Anti-lock Braking System Option	STND
Security System Option	STND
Cruise Control Option	STND
California Emissions	\$200
Freight <sup>2</sup>	\$435

## FLTRUSE CVO™ ROAD GLIDE® ULTRA

<b>MSRP</b> Custom	<b>\$39,649</b>
Anti-lock Braking System Option	STND
Security System Option	STND
Cruise Control Option	STND
Premium Radio Option	STND
California Emissions	\$200
Freight <sup>2</sup>	\$435

## FLHXSE CVO™ STREET GLIDE®

<b>MSRP</b> Custom	<b>\$36,349</b>
Anti-lock Braking System Option	STND
Security System Option	STND
Cruise Control Option	STND
Premium Radio Option	STND
California Emissions	\$200
Freight <sup>2</sup>	\$435

<sup>1</sup> 49-state only. Prices listed are the Manufacturer's Suggested Retail Prices.  
Options such as color and fuel systems are available at additional cost.  
Prices exclude dealer setup, taxes, title and licensing and are subject to change.  
Dealer prices may vary.

<sup>2</sup> Freight price applies to the 48 contiguous states and Alaska only.