

STREET BOB®

FXDB

MODEL SPECIFICATIONS¹



DIMENSIONS	
Length	94.3 in. (2395 mm)
Overall Width	36 in. (915 mm)
Overall Height	48.8 in. (1240 mm)
Seat Height:	
• Laden²	25.5 in. (648 mm)
• Unladen	26.8 in. (680 mm)
Ground Clearance	4.7 in. (120 mm)
Rake (steering head)	29°
Fork Angle	29°
Trail	4.7 in. (119 mm)
Wheelbase	64.2 in. (1630 mm)
Tires (Michelin® Scorcher® “31” front and rear):	
• Front – Scorcher® “31” 100/90B19 57H	
• Rear – Scorcher® “31” 160/70B17 73V	
Fuel Capacity	4.7 gal. (17.8 L)
(warning light at approximately 0.9 gal.)	
Oil Capacity (w/filter)	3 qts. (2.8 L)
Transmission Capacity	1 qt. (.95 L)
Primary Chain Case Capacity	1 qt. (.95 L)
Weight:	
• As Shipped	637 lbs. (289 kg)
• In Running Order	670 lbs. (304 kg)
• Gross Vehicle Weight Rating	1085 lbs. (492 kg)
• Gross Axle Weight Rating:	
• Front	390 lbs. (177 kg)
• Rear	695 lbs. (315 kg)
ENGINE	
Engine	Air-cooled, Twin Cam 103™
Valves	Pushrod-operated, overhead valves with hydraulic, self-adjusting lifters; two valves per cylinder
Bore x Stroke	3.875 in. x 4.375 in. (98.4 mm x 111.1 mm)
Displacement	103.1 cu. in. (1690 cc)
Compression Ratio	9.6:1
Fuel System³	Electronic Sequential Port Fuel Injection (ESPFI)
Air Cleaner	Fiberglass media, washable
Lubrication System	Pressurized, dry-sump

DRIVETRAIN	
Primary Drive	Chain, 34/46 ratio
Final Drive	Belt, 32/66 ratio
Clutch	Multi-plate, wet
Transmission	6-Speed Cruise Drive®
Gear Ratios (overall):	U.S.
• 1st	9.311
• 2nd	6.454
• 3rd	4.793
• 4th	3.882
• 5th	3.307
• 6th	2.79
CHASSIS	
Frame	Mild steel, tubular frame; rectangular section backbone; stamped, cast, and forged junctions; forged fender supports; MIG welded
Swingarm	Mild steel, rectangular tube sections, stamped junctions; MIG welded
Front Forks	49 mm with polished aluminum fork triple clamp and dual-rate springs
Rear Shocks	Coil-over shock
Wheels⁴:	Black Steel Laced
• Front	19 in. x 2.5 in. (483 mm x 64 mm)
• Rear	17 in. x 4.5 in. (432 mm x 114 mm)
Brakes:	
• Caliper Type	4-piston fixed front, and 2-piston torque-free floating rear
• Rotor Type (diameter x width):	Patented, uniform expansion rotors (floating, front only)
• Front (floating)	11.8 in. x .2 in. (300 mm x 5.1 mm)
• Rear	11.5 in. x .23 in. (292 mm x 5.8 mm)
• Anti-lock Braking System	Optional
Suspension Travel:	
• Front Wheel	5 in. (127 mm)
• Rear Wheel	3.1 in. (80 mm)
PERFORMANCE	
Engine Torque⁵ (per J1349):	
• North America	98.8 ft. lbs. @ 3000 RPM (134 Nm @ 3000 RPM)
Lean Angle (per J1168):	
• Right	30°
• Left	31°
Fuel Economy⁶	43 mpg (5.5 L/100 km)
(EPA urban/highway test)	

ELECTRIC	
Battery (per Battery Council International Rating)	Sealed, maintenance-free, 12V, 19-amp/hour, 270 cca
Charging	Three-phase, 40-amp system (493W @ 13.5V, 2000 RPM, 540W max power @ 13.5V)
Starting	1.2 kW electric with solenoid shift starter motor engagement
Lights (as per country regulation):	
• Headlamp (Quartz Halogen)	55-watt low beam, 60-watt high beam
• Rear Tail/Stop/Turn Signal Lights	9W/43W self-canceling
• Indicator Lamps	High beam, directional light bar, neutral, low oil pressure, engine diagnostics, turn signals, security system⁷ (optional), 6-speed, low fuel warnings
WARRANTY	
Warranty⁸	24 months (unlimited mileage)
Service Interval⁹	First 1000 miles (1600 km), every 5000 miles (8000 km) thereafter

¹ Vehicles depicted may differ from vehicles manufactured and delivered. Specifications and prices listed may differ from specifications and prices of vehicles manufactured and delivered. All product descriptions (including depictions, specifications, dimensions, measurements, ratings and competitive comparisons) are based on available information at the time of publication. Although such descriptions are believed correct, errors and changes can occur and complete accuracy cannot be guaranteed. Harley-Davidson may make changes at any time to prices and specifications, and may change or discontinue models, without notice and without incurring any obligation. Attention: Vehicles in the configurations shown and many of the accessories described in this catalog may not be available for sale or use in some locations. Please check with your dealer for complete product details and the latest information. All models feature 6-speed transmission (V-Rod® models and Sportster® models are 5-speed) and carbon fiber belt final drive; multi-plate clutch with diaphragm spring in oil bath; and 2-year unlimited mileage warranty.

² Measurement reflects **180 lb.** (81.7 kg) operator weight.

³ Recommended 91 octane or higher fuel (R+M)/2.

⁴ Standard and optional wheels may vary by country and region.

⁵ Values shown are nominal. Performance may vary by country and region.

⁶ The combined fuel economy numbers were derived using a combination of estimated city and highway values. Fuel economy estimates are derived from US EPA exhaust emission certification data on a sample motorcycle from the corresponding family under ideal laboratory conditions. Your actual fuel economy will vary depending on your personal riding habits, road and driving conditions, vehicle condition and maintenance, tire pressure, vehicle configuration (parts and accessories), and vehicle loading (cargo, rider and passenger weight). Break-in mileage may vary.

⁷ North America security system includes immobilizer; outside North America the security system includes immobilizer and siren.

⁸ See motorcycle owner's manual for complete details.

⁹ Inspections of certain systems and components are required at 2,500 mile (4,000 km) intervals. See Owner's Manual for full details.

FAT BOB®

MODEL SPECIFICATIONS¹



DIMENSIONS	
Length	94.5 in. (2400 mm)
Overall Width	35 in. (890 mm)
Overall Height	44.7 in. (1135 mm)
Seat Height:	
• Laden²	26.1 in. (663 mm)
• Unladen	27.2 in. (690 mm)
Ground Clearance	4.9 in. (125 mm)
Rake (steering head)	29°
Fork Angle	28°
Trail	4.9 in. (125 mm)
Wheelbase	63.8 in. (1620 mm)
Tires (Dunlop® Harley-Davidson® Series, bias blackwall front and rear):	
• Front – D427F	130/90B16 67H
• Rear – D427	180/70B16 77H
Fuel Capacity	5 gal. (18.9 L)
(warning light at approximately 0.9 gal.)	
Oil Capacity (w/filter)	3 qts. (2.8 L)
Transmission Capacity	1 qt. (.95 L)
Primary Chain	1 qt. (.95 L)
Case Capacity	
Weight:	
• As Shipped	673 lbs. (305 kg)
• In Running Order	706 lbs. (320 kg)
• Gross Vehicle Weight Rating	1085 lbs. (492 kg)
• Gross Axle Weight Rating:	
• Front	390 lbs. (177 kg)
• Rear	695 lbs. (315 kg)
ENGINE	
Engine	Air-cooled, Twin Cam 103™
Valves	Pushrod-operated, overhead valves with hydraulic, self-adjusting lifters; two valves per cylinder
Bore x Stroke	3.87 in. x 4.38 in. (98.4 mm x 111.1 mm)
Displacement	103.1 cu. in. (1690 cc)
Compression Ratio	9.6:1
Fuel System³	Electronic Sequential Port Fuel Injection (ESPFI)
Air Cleaner	Fiberglass media, washable
Lubrication System	Pressurized, dry-sump

DRIVETRAIN	
Primary Drive	Chain, 34/46 ratio
Final Drive	Belt, 32/66 ratio
Clutch	Multi-plate, wet
Transmission	6-Speed Cruise Drive®
Gear Ratios (overall):	U.S.
• 1st	9.311
• 2nd	6.454
• 3rd	4.793
• 4th	3.882
• 5th	3.307
• 6th	2.79

CHASSIS	
Frame	Mild steel, tubular frame; rectangular section backbone; stamped, cast, and forged junctions; forged fender supports; MIG welded
Swingarm	Mild steel, rectangular tube sections, stamped junctions; MIG welded
Front Forks	49 mm with polished aluminum fork triple clamp and dual-rate springs
Rear Shocks	Fully covered, coil-over shock
Wheels⁴:	Gloss Black Cast Aluminum Wheel with laser-engraved graphics
• Front	16 in. x 3 in. (406 mm x 76 mm)
• Rear	16 in. x 5 in. (406 mm x 127 mm)
Brakes:	
• Caliper Type	4-piston fixed front, and 2-piston torque-free floating rear
• Rotor Type (diameter x width):	Patented, uniform expansion rotors (floating, front only)
• Front (dual floating)	11.8 in. x .2 in. (300 mm x 5.1 mm)
• Rear	11.5 in. x .23 in. (292 mm x 5.8 mm)
• Anti-lock Braking System	Optional
Suspension Travel:	
• Front Wheel	5 in. (127 mm)
• Rear Wheel	2.13 in. (55 mm)

PERFORMANCE	
Engine Torque⁵ (per J1349):	
• North America	98.8 ft. lbs. @ 3500 RPM (134 Nm @ 3500 RPM)
Lean Angle (per J1168):	
• Right	30°
• Left	31°
Fuel Economy⁶	42 mpg (5.6 L/100 km)
(EPA urban/highway test)	

ELECTRIC	
Battery (per Battery Council International Rating)	Sealed, maintenance-free, 12V, 19-amp/hour, 270 cca
Charging	Three-phase, 40-amp system (493W @ 13.5V, 2000 RPM, 540W max power @ 13.5V)
Starting	1.2 kW electric with solenoid shift starter motor engagement
Lights (as per country regulation):	
• Headlamp (Dual Quartz Halogen)	55-watt low beam, 60-watt high beam
• Tail/Stop Lights	Integrated LED
• Turn Signal Lights	28W self-canceling
• Indicator Lamps	High beam, directional light bar, neutral, low oil pressure, engine diagnostics, turn signals, security system⁷ (optional), 6-speed, low fuel warnings
WARRANTY	
Warranty⁸	24 months (unlimited mileage)
Service Interval⁹	First 1000 miles (1600 km), every 5000 miles (8000 km) thereafter

¹ Vehicles depicted may differ from vehicles manufactured and delivered. Specifications and prices listed may differ from specifications and prices of vehicles manufactured and delivered. All product descriptions (including depictions, specifications, dimensions, measurements, ratings and competitive comparisons) are based on available information at the time of publication. Although such descriptions are believed correct, errors and changes can occur and complete accuracy cannot be guaranteed. Harley-Davidson may make changes at any time to prices and specifications, and may change or discontinue models, without notice and without incurring any obligation. Attention: Vehicles in the configurations shown and many of the accessories described in this catalog may not be available for sale or use in some locations. Please check with your dealer for complete product details and the latest information. All models feature 6-speed transmission (V-Rod® models and Sportster® models are 5-speed) and carbon fiber belt final drive; multi-plate clutch with diaphragm spring in oil bath; and 2-year unlimited mileage warranty.

² Measurement reflects **180 lb.** (81.7 kg) operator weight.

³ Recommended 91 octane or higher fuel (R+M)/2.

⁴ Standard and optional wheels may vary by country and region.

⁵ Values shown are nominal. Performance may vary by country and region.

⁶ The combined fuel economy numbers were derived using a combination of estimated city and highway values. Fuel economy estimates are derived from US EPA exhaust emission certification data on a sample motorcycle from the corresponding family under ideal laboratory conditions. Your actual fuel economy will vary depending on your personal riding habits, road and driving conditions, vehicle condition and maintenance, tire pressure, vehicle configuration (parts and accessories), and vehicle loading (cargo, rider and passenger weight). Break-in mileage may vary.

⁷ North America security system includes immobilizer; outside North America the security system includes immobilizer and siren.

⁸ See motorcycle owner's manual for complete details.

⁹ Inspections of certain systems and components are required at 2,500 mile (4,000 km) intervals. See Owner's Manual for full details.

FXDL LOW RIDER® MODEL SPECIFICATIONS¹



DIMENSIONS	
Length	92.3 in. (2345 mm)
Overall Width	35.6 in. (905 mm)
Overall Height	46.6 in. (1185 mm)
Seat Height:	
• Laden²	25.4 in. (660 mm)
• Unladen	26.8 in. (680 mm)
Ground Clearance	4.13 in. (105 mm)
Rake (steering head)	30.5°
Fork Angle	32°
Trail	5.1 in. (128.3 mm)
Wheelbase	64.2 in. (1630 mm)
Tires (Michelin® Scorcher® “31” front and rear):	
• Front – Scorcher® “31”	100/90B19 57H
• Rear – Scorcher® “31”	160/70B17 73V
Fuel Capacity	4.7 gal. (17.8 L)
(warning light at approximately 0.9 gal.)	
Oil Capacity (w/filter)	3 qts. (2.8 L)
Transmission Capacity	1 qt. (.95 L)
Primary Chain	1 qt. (.95 L)
Case Capacity	
Weight:	
• As Shipped	644 lbs. (292 kg)
• In Running Order	666 lbs. (302 kg)
• Gross Vehicle Weight Rating	1085 lbs. (492 kg)
• Gross Axle Weight Rating:	
• Front	390 lbs. (177 kg)
• Rear	695 lbs. (315 kg)
ENGINE	
Engine	Air-cooled, Twin Cam 103™
Valves	Pushrod-operated, overhead valves with hydraulic, self-adjusting lifters; two valves per cylinder
Bore x Stroke	3.87 in. x 4.374 in. (98.4 mm x 111.1 mm)
Displacement	103.1 cu. in. (1690 cc)
Compression Ratio	9.6:1
Fuel System³	Electronic Sequential Port Fuel Injection (ESPFI)
Air Cleaner	Fiberglass media, washable
Lubrication System	Pressurized, dry-sump

DRIVETRAIN	
Primary Drive	Chain, 34/46 ratio
Final Drive	Belt, 32/66 ratio
Clutch	Multi-plate, wet
Transmission	6-Speed Cruise Drive®
Gear Ratios (overall):	U.S.
• 1st	9.311
• 2nd	6.454
• 3rd	4.793
• 4th	3.882
• 5th	3.307
• 6th	2.79
CHASSIS	
Frame	Mild steel, tubular frame; rectangular section backbone; stamped, cast, and forged junctions; forged fender supports; MIG welded
Swingarm	Mild steel, rectangular tube sections, stamped junctions; MIG welded
Front Forks	49 mm with polished aluminum fork triple clamp and dual-rate springs
Rear Shocks	Coil-over shock with tri-rate springs
Wheels	Wheels⁴ (Chrome Steel Laced option):
• Front	19 in. x 2.5 in. (483 mm x 64 mm)
• Rear	17 in. x 4.5 in. (432 mm x 114 mm)
Brakes:	
• Caliper Type	4-piston fixed front, and 2-piston torque-free floating rear
• Rotor Type (diameter x width):	Patented, uniform expansion rotors (floating, front only)
• Front (dual floating)	11.8 in. x .2 in. (300 mm x 5.1 mm)
• Rear	11.5 in. x .23 in. (292 mm x 5.8 mm)
• Anti-lock Braking System	Optional
Suspension Travel:	
• Front Wheel	5.1 in. (130 mm)
• Rear Wheel	3.1 in. (79 mm)
PERFORMANCE	
Engine Torque⁵ (per J1349):	
• North America	98.8 ft. lbs. @ 3500 RPM (134 Nm @ 3500 RPM)
Lean Angle (per J1168):	
• Right	29.5°
• Left	30.5°
Fuel Economy⁶	43 mpg (5.5 L/100 km)
(EPA urban/highway test)	

ELECTRIC	
Battery (per Battery Council International Rating)	Sealed, maintenance-free, 12V, 19-amp/hour, 270 cca
Charging	Three-phase, 40-amp system (493W @ 13.5V, 2000 RPM, 540W max power @ 13.5V)
Starting	1.2kW electric with solenoid shift starter motor engagement
Lights (as per country regulation):	
• Headlamp (Quartz Halogen)	55-watt low beam, 60-watt high beam
• Tail/Stop Lights	8W/28W
• Turn Signal Lights	28W self-canceling
• Indicator Lamps	High beam, directional light bar, neutral, low oil pressure, engine diagnostics, turn signals, security system⁷ (optional), 6-speed, low fuel warnings
WARRANTY	
Warranty⁸	24 months (unlimited mileage)
Service Interval⁹	First 1000 miles (1600 km), every 5000 miles (8000 km) thereafter

¹ Vehicles depicted may differ from vehicles manufactured and delivered. Specifications and prices listed may differ from specifications and prices of vehicles manufactured and delivered. All product descriptions (including depictions, specifications, dimensions, measurements, ratings and competitive comparisons) are based on available information at the time of publication. Although such descriptions are believed correct, errors and changes can occur and complete accuracy cannot be guaranteed. Harley-Davidson may make changes at any time to prices and specifications, and may change or discontinue models, without notice and without incurring any obligation. Attention: Vehicles in the configurations shown and many of the accessories described in this catalog may not be available for sale or use in some locations. Please check with your dealer for complete product details and the latest information. All models feature 6-speed transmission (V-Rod® models and Sportster® models are 5-speed) and carbon fiber belt final drive; multi-plate clutch with diaphragm spring in oil bath; and 2-year unlimited mileage warranty.

² Measurement reflects **180 lb.** (81.7 kg) operator weight.

³ Recommended 91 octane or higher fuel (R+M)/2.

⁴ Standard and optional wheels may vary by country and region.

⁵ Values shown are nominal. Performance may vary by country and region.

⁶ The combined fuel economy numbers were derived using a combination of estimated city and highway values. Fuel economy estimates are derived from US EPA exhaust emission certification data on a sample motorcycle from the corresponding family under ideal laboratory conditions. Your actual fuel economy will vary depending on your personal riding habits, road and driving conditions, vehicle condition and maintenance, tire pressure, vehicle configuration (parts and accessories), and vehicle loading (cargo, rider and passenger weight). Break-in mileage may vary.

⁷ See motorcycle owner's manual for complete details.

⁸ Inspections of certain systems and components are required at 2,500 mile (4,000 km) intervals. See Owner's Manual for full details.

FXDWG

WIDE GLIDE®

MODEL SPECIFICATIONS¹



DIMENSIONS	
Length	96.3 in. (2445 mm)
Overall Width	35.2 in. (895 mm)
Overall Height	44.7 in. (1135 mm)
Seat Height:	
• Laden²	25.5 in. (648 mm)
• Unladen	26.8 in. (680 mm)
Ground Clearance	3.9 in. (100 mm)
Rake (steering head)	34°
Fork Angle	36°
Trail	5.2 in. (132 mm)
Wheelbase	67.5 in. (1715 mm)
Tires (Michelin® Scorcher® "31" front and rear):	
• Front – Scorcher® "31"	80/90-21 54H
• Rear – Scorcher® "31"	180/60B17 75V
Fuel Capacity	4.7 gal. (17.8 L)
(warning light at approximately 0.9 gal.)	
Oil Capacity (w/filter)	3 qts. (2.8 L)
Transmission Capacity	1 qt. (.95 L)
Primary Chain	1 qt. (.95 L)
Case Capacity	
Weight:	
• As Shipped	650 lbs. (295 kg)
• In Running Order	683 lbs. (310 kg)
• Gross Vehicle Weight Rating	1085 lbs. (492 kg)
• Gross Axle Weight Rating:	
• Front	390 lbs. (177 kg)
• Rear	695 lbs. (315 kg)
ENGINE	
Engine	Air-cooled, Twin Cam 103™
Valves	Pushrod-operated, overhead valves with hydraulic, self-adjusting lifters; two valves per cylinder
Bore x Stroke	3.875 in. x 4.374 in. (98.4 mm x 111.1 mm)
Displacement	103.1 cu. in. (1690 cc)
Compression Ratio	9.6:1
Fuel System³	Electronic Sequential Port Fuel Injection (ESPFI)
Air Cleaner	Fiberglass media, washable
Lubrication System	Pressurized, dry-sump

DRIVETRAIN	
Primary Drive	Chain, 34/46 ratio
Final Drive	Belt, 32/66 ratio
Clutch	Multi-plate, wet
Transmission	6-Speed Cruise Drive®
Gear Ratios (overall):	U.S.
• 1st	9.311
• 2nd	6.454
• 3rd	4.793
• 4th	3.882
• 5th	3.307
• 6th	2.79
CHASSIS	
Frame	Mild steel, tubular frame; rectangular section backbone; stamped, cast, and forged junctions; forged fender supports; MIG welded
Swingarm	Mild steel, rectangular tube sections, stamped junctions; MIG welded
Front Forks	49 mm with polished aluminum fork triple clamp and dual-rate springs
Rear Shocks	Coil-over shock
Wheels⁴:	Black Steel Laced
• Front	21 in. x 2.15 in. (533 mm x 55 mm)
• Rear	17 in. x 4.5 in. (432 mm x 114 mm)
Brakes:	
• Caliper Type	4-piston front and 2-piston torque-free floating rear
• Rotor Type (diameter x width):	Patented, uniform expansion rotors (floating, front only)
• Front (floating)	11.8 in. x .2 in. (300 mm x 5.1 mm)
• Rear	11.5 in. x .23 in. (292 mm x 5.8 mm)
• Anti-lock Braking System	Standard
Suspension Travel:	
• Front Wheel	5 in. (127 mm)
• Rear Wheel	3.1 in. (80 mm)
PERFORMANCE	
Engine Torque⁵ (per J1349):	
• North America	98.8 ft. lbs. @ 3500 RPM (134 Nm @ 3500 RPM)
Lean Angle (per J1168):	
• Right	28.4°
• Left	31.9°
Fuel Economy⁶	42 mpg (5.6 L/100 km)
(EPA urban/highway test)	

ELECTRIC	
Battery (per Battery Council International Rating)	Sealed, maintenance-free, 12V, 19-amp/hour, 270 cca
Charging	Three-phase, 40-amp system (493W @ 13.5V, 2000 RPM, 540W max power @ 13.5V)
Starting	1.2 kW electric with solenoid shift starter motor engagement
Lights (as per country regulation):	
• Headlamp (Quartz Halogen)	55-watt low beam, 60-watt high beam
• Rear Tail/Stop/Turn Signal Lights	9W/43W self-canceling
• Indicator Lamps	High beam, directional light bar, neutral, low oil pressure, engine diagnostics, turn signals, security system⁷ (optional), 6-speed, low fuel warnings
WARRANTY	
Warranty⁸	24 months (unlimited mileage)
Service Interval⁹	First 1000 miles (1600 km), every 5000 miles (8000 km) thereafter

¹ Vehicles depicted may differ from vehicles manufactured and delivered. Specifications and prices listed may differ from specifications and prices of vehicles manufactured and delivered. All product descriptions (including depictions, specifications, dimensions, measurements, ratings and competitive comparisons) are based on available information at the time of publication. Although such descriptions are believed correct, errors and changes can occur and complete accuracy cannot be guaranteed. Harley-Davidson may make changes at any time to prices and specifications, and may change or discontinue models, without notice and without incurring any obligation. Attention: Vehicles in the configurations shown and many of the accessories described in this catalog may not be available for sale or use in some locations. Please check with your dealer for complete product details and the latest information. All models feature 6-speed transmission (V-Rod® models and Sportster® models are 5-speed) and carbon fiber belt final drive; multi-plate clutch with diaphragm spring in oil bath; and 2-year unlimited mileage warranty.

² Measurement reflects **180 lb.** (81.7 kg) operator weight.

³ Recommended 91 octane or higher fuel (R+M)/2.

⁴ Standard and optional wheels may vary by country and region.

⁵ Values shown are nominal. Performance may vary by country and region.

⁶ The combined fuel economy numbers were derived using a combination of estimated city and highway values. Fuel economy estimates are derived from US EPA exhaust emission certification data on a sample motorcycle from the corresponding family under ideal laboratory conditions. Your actual fuel economy will vary depending on your personal riding habits, road and driving conditions, vehicle condition and maintenance, tire pressure, vehicle configuration (parts and accessories), and vehicle loading (cargo, rider and passenger weight). Break-in mileage may vary.

⁷ North America security system includes immobilizer; outside North America the security system includes immobilizer and siren.

⁸ See motorcycle owner's manual for complete details.

⁹ Inspections of certain systems and components are required at 2,500 mile (4,000 km) intervals. See Owner's Manual for full details.

FLD SWITCHBACK™ MODEL SPECIFICATIONS¹



DIMENSIONS	
Length	92.9 in. (2360 mm)
Overall Width	36.6 in. (930 mm)
Overall Height	54.5 in. (1385 mm)
Seat Height:	
• Laden²	26.1 in. (663 mm)
• Unladen	27.4 in. (695 mm)
Ground Clearance	4.3 in. (110 mm)
Rake (steering head)	29.9°
Fork Angle	28.9°
Trail	5.8 in. (148 mm)
Wheelbase	62.8 in. (1595 mm)
Tires (Dunlop® Harley-Davidson® Series, bias blackwall front and rear):	
• Front – Dunlop® D402F 130/70B18 63H	
• Rear – Dunlop® D401 160/70B17 73H	
Fuel Capacity	4.7 gal. (17.8 L)
(warning light at approximately 0.9 gal.)	
Oil Capacity (w/filter)	3 qts. (2.8 L)
Transmission Capacity	1 qt. (.95 L)
Primary Chain	1 qt. (.95 L)
Case Capacity	
Weight:	
• As Shipped	696 lbs. (316 kg)
• In Running Order	718 lbs. (326 kg)
• Gross Vehicle Weight Rating	1170 lbs. (530 kg)
• Gross Axle Weight Rating:	
• Front	455 lbs. (206 kg)
• Rear	794 lbs. (360 kg)
ENGINE	
Engine	Air-cooled, Twin Cam 103™
Valves	Pushrod-operated, overhead valves with hydraulic, self adjusting lifters; two valves per cylinder
Bore x Stroke	3.87 in. x 4.374 in. (98.4 mm x 111.1 mm)
Displacement	103.1 cu. in. (1690 cc)
Compression Ratio	9.6:1
Fuel System³	Electronic Sequential Port Fuel Injection (ESPFI)
Air Cleaner	Fiberglass media, washable
Lubrication System	Pressurized, dry-sump

DRIVETRAIN	
Primary Drive	Chain, 34/46 ratio
Final Drive	Belt, 32/66 ratio
Clutch	Multi-plate, wet
Transmission	6-Speed Cruise Drive®
Gear Ratios (overall):	U.S.
• 1st	9.311
• 2nd	6.454
• 3rd	4.793
• 4th	3.882
• 5th	3.307
• 6th	2.79
CHASSIS	
Frame	Mild steel, tubular frame; rectangular section backbone; stamped, cast, and forged junctions; forged fender supports; MIG welded
Swingarm	Mild steel, rectangular tube sections backbone; stamped junctions; MIG welded
Front Forks	41.3 mm fork with 20 mm cartridge damping and triple rate spring
Rear Shocks	Nitrogen charged 36 mm monotube damper with 5 step preload adjustable dual rate spring
Wheels⁴:	Black 5-Spoke Cast Aluminum with highlighted rim
• Front	18 in. x 3.5 in. (457 mm x 89 mm)
• Rear	17 in. x 4.5 in. (432 mm x 114 mm)
Brakes:	
• Caliper Type	4-piston fixed front, and 2-piston torque-free floating rear
• Rotor Type (diameter x width):	Patented, uniform expansion rotors (floating, front only)
• Front (floating)	11.8 in. x .2 in. (300 mm x 5.1 mm)
• Rear	11.5 in. x .2 in. (292 mm x 5.1 mm)
• Anti-lock Braking System	Standard
Suspension Travel:	
• Front Wheel	3.9 in. (98 mm)
• Rear Wheel	2.1 in. (54 mm)

PERFORMANCE	
Engine Torque⁵ (per J1349):	
• North America	98.8 ft. lbs. @ 3500 RPM (134 Nm @ 3500 RPM)
Lean Angle (per J1168):	
• Right	29°
• Left	29°
Fuel Economy⁶ (EPA urban/highway test)	42 mpg (5.6 L/100 km)
ELECTRIC	
Battery (per Battery Council International Rating)	Sealed, maintenance-free, 12V, 19-amp/hour, 270 cca
Charging	Three-phase, 40-amp system (493W @ 13.5V, 2000 RPM, 540W max power @ 13.5V)
Starting	1.2kW electric with solenoid shift starter motor engagement
Lights (as per country regulation):	
• Headlamp (Quartz Halogen)	55-watt low beam, 60-watt high beam
• Tail/Stop Lights	8W/28W
• Turn Signal Lights	28W self-canceling
• Indicator Lamps	High beam, neutral, low oil pressure, engine diagnostics, turn signals, low fuel warning, ABS (optional), low battery, body controller diagnostics
WARRANTY	
Warranty⁷	24 months (unlimited mileage)
Service Interval⁸	First 1000 miles (1600 km), every 5000 miles (8000 km) thereafter

¹ Vehicles depicted may differ from vehicles manufactured and delivered. Specifications and prices listed may differ from specifications and prices of vehicles manufactured and delivered. All product descriptions (including depictions, specifications, dimensions, measurements, ratings and competitive comparisons) are based on available information at the time of publication. Although such descriptions are believed correct, errors and changes can occur and complete accuracy cannot be guaranteed. Harley-Davidson may make changes at any time to prices and specifications, and may change or discontinue models, without notice and without incurring any obligation. Attention: Vehicles in the configurations shown and many of the accessories described in this catalog may not be available for sale or use in some locations. Please check with your dealer for complete product details and the latest information. All models feature 6-speed transmission (V-Rod® models and Sportster® models are 5-speed) and carbon fiber belt final drive; multi-plate clutch with diaphragm spring in oil bath; and 2-year unlimited mileage warranty.

² Measurement reflects **180 lb.** (81.7 kg) operator weight.

³ Recommended 91 octane or higher fuel (R+M)/2.

⁴ Standard and optional wheels may vary by country and region.

⁵ Values shown are nominal. Performance may vary by country and region.

⁶ The combined fuel economy numbers were derived using a combination of estimated city and highway values. Fuel economy estimates are derived from US EPA exhaust emission certification data on a sample motorcycle from the corresponding family under ideal laboratory conditions. Your actual fuel economy will vary depending on your personal riding habits, road and driving conditions, vehicle condition and maintenance, tire pressure, vehicle configuration (parts and accessories), and vehicle loading (cargo, rider and passenger weight). Break-in mileage may vary.

⁷ See motorcycle owner's manual for complete details.

⁸ Inspections of certain systems and components are required at 2,500 mile (4,000 km) intervals. See Owner's Manual for full details.

2015

DYNA® FAMILY

MANUFACTURER'S SUGGESTED RETAIL PRICE (MSRP)¹

FXDB STREET BOB®

A Minimalist Bobber, Featuring Optional H-D1™ Factory Customization

MSRP Vivid Black	\$13,449
MSRP Color	\$13,849
MSRP Hard Candy Custom	\$14,199
ABS Option	\$795
Security System Option	\$395
California Emissions	\$200
Freight ²	\$390

FXDF FAT BOB®

A Beast with Big Power and Unmistakable Attitude

MSRP Vivid Black	\$15,699
MSRP Color	\$16,099
ABS Option	\$795
Security System Option	\$395
California Emissions	\$200
Freight ²	\$390

FXDL LOW RIDER®

An Original American Icon, Rediscovered

MSRP Vivid Black	\$14,199
MSRP Color	\$14,599
MSRP Two-Tone	\$14,949
MSRP Custom Color	\$15,149
ABS Option	\$795
Wheel Option	\$460
Security System Option	\$395
California Emissions	\$200
Freight ²	\$390

FXDWG WIDE GLIDE®

Long and Skinny Up Front. Fat and Low in the Back. Authentic and Tough All Over

MSRP Vivid Black	\$15,799
MSRP Flame	\$16,549
MSRP Custom Color	\$16,749
ABS Option	STND
Security System Option	\$395
California Emissions	\$200
Freight ²	\$390

FLD SWITCHBACK™

Cruising and Touring – Two Bikes in One with No Compromises

MSRP Vivid Black	\$16,999
MSRP Color	\$17,399
ABS Option	STND
Security System Option	\$395
California Emissions	\$200
Freight ²	\$390

¹ 49-state only. Prices listed are the Manufacturer's Suggested Retail Prices. Options such as color and fuel systems are available at additional cost. Prices exclude dealer setup, taxes, title and licensing and are subject to change.

² Freight price applies to the 48 contiguous states and Alaska only.