

# Rigid 14 Shower Walls

## Rigid 14 Shower Walls

Designed as a thick sandwich panel with a foam core and additional solid PET layer. The panel is stronger and stiffer than the Flex 14. Ideal for larger surfaces and complete walls. Requires a support structure but does not require a continuous structure or smooth surface.

### Recommendations

**Adhesive:** Soudal XF250 is the recommended choice due to good initial adhesion, ample adjustment time and swift curing time. However, the majority of conventional silicone adhesives are also suitable.

**Tools:** Drills, saws and routers have all been tested on the material. We recommend fine-toothed saws over large teeth as this may leave the panel torn or shredded.

**Finishing:** For corners, end pieces and trims we offer custom solutions.

### Dimensions

**Total Thickness:** 14mm  
**Core Thickness:** 8mm  
**Face Thickness:** 3mm  
**Width:** 1200mm or 600mm  
**Length:** 2420mm

### Material

**Decorative Film:** 99% recycled PET  
**Top Solid Layer:** 50% recycled PET  
**Foam Core:** 99% recycled PET  
**Bottom Solid Layer:** n.a

### Weight & Density

**Core Density:** 70kg/m<sup>3</sup>  
**Face Density:** 1380kg/m<sup>3</sup>  
**Panel Weight:** 8.36kg/m<sup>2</sup>

